

PRODUCT DESCRIPTION

Oculus Lubricant GX-5 Motor Oil is a multi-grade advanced version of Gasoline and CNG Engine Oil. It is formulated to combat high temperature caused by dry combustion in Gasoline and CNG fuel operated engines and ensures excellent engine performance under all climatic conditions. It provides optimum protection against oxidation and gives improved drain interval.

APPLICATIONS

- Developed for naturally aspirated or turbocharged vehicles operating under moderate to severe working and load conditions.

PERFORMANCE STANDARD

The superior additive package used in the formulation of Oculus Lubricant GX-5 Motor Oil endorses the following performance standards:

API SG/CD

BENEFITS

- Superior protection of engine parts against high temperatures in Gasoline and CNG vehicles.
- Special antioxidant additive reduces sludge formation and increases oil drain interval.
- Equally suited for both CNG and gasoline engines.
- Provides extra protection against valve wear.

PRODUCT CHARACTERISTICS*

PROPERTIES	METHOD	TYPICAL RESULTS – 20W-50
Density @ 15 °C, Kg/liter	ASTM D-4052	0.8962
Kinematic Viscosity @ 100 °C, cSt	ASTM D-445	19.5
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	181
Viscosity Index	ASTM D-2270	121
Flash Point (COC), °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-21
Total Base Number, mg KOH/g	ASTM D-2896	7

* These typical characteristics mentioned are based on current mean values.



HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from Oculus Lubricant representative.



ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



ADVICE

Advice on application not covered in this leaflet, may be obtained from Oculus Lubricant representative.