

## PRODUCT DESCRIPTION

Oculus Lubricant MGX 1000 is a high performance and high detergency lubricant especially developed to meet the stringent requirements of diesel engines where API CC/SD oil is recommended.

## APPLICATIONS

- Suitable for applications requiring performance level of API classification CC/SD.
- Appropriate choice for a wide variety of diesel engine vehicles for agricultural and off-road applications.
- Suitable to use in heavy and light commercial vehicles.

## PERFORMANCE STANDARD

The superior additive technology used in the formulation of Oculus Lubricant MGX 1000 endorses the following performance standard:

API CC/SD

## BENEFITS

- Effective control of engine wear and deposits on engine parts.
- An economical product with good all-round performance.
- Protects against rust and corrosion.

## PRODUCT CHARACTERISTICS\*

PROPERTIES	METHOD	TYPICAL RESULTS - 50
Density @ 15 °C, Kg/liter	ASTM D-4052	0.9252
Kinematic Viscosity @100 °C, cSt	ASTM D-445	19.87
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	250.5
Viscosity Index	ASTM D-2270	91
Flash Point (COC), °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-6
Total Base Number, mg KOH/g	ASTM D-2896	9.1

\* These typical characteristics mentioned are based on current mean values.



### HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from Oculus Lubricant representative.



### ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



### ADVICE

Advice on application not covered in this leaflet, may be obtained from Oculus Lubricant representative.