

PRODUCT DESCRIPTION

Oculus Lubricant MGX 2000 diesel engine oil series is formulated for the lubrication of engines used in general transport for carrying heavy goods, earth-moving, quarrying, construction equipment and agricultural machinery well as for stationary diesel engines where API CD/SF performance is recommended. These high detergency lubricants are manufactured with high quality refined base oils and a superior-performance additive package to meet stringent requirements of diesel engines.

APPLICATIONS

- Beneficial for automobiles fleet operating on diesel fuel.
- Heavy duty vehicles in general transport.
- Construction and earthmoving equipment.
- Light trucks, mini buses & agricultural equipment having diesel engines.
- Older models diesel engine passenger cars.

PERFORMANCE STANDARD

Superior additive technology used in formulation of Oculus Lubricant MGX 2000 endorses the following performance standard:

API CD/SF

BENEFITS

- Formulated for diesel engines operating under the most demanding conditions.
- Additional engine protection and performance.
- Keeps the engine clean and extends engine service life.
- Protects against soot, varnish, sludge formation and corrosion.
- Improved protection against high-temperature, especially in hot and dusty climate.

PRODUCT CHARACTERISTICS*

PROPERTIES	METHOD	30	40	50
		Density @ 15 °C, Kg/liter	ASTM D-4052	0.8973
Kinematic Viscosity @100 °C, cSt	ASTM D-445	10.7	14.7	19.6
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	90.3	146.6	225.3
Viscosity Index	ASTM D-2270	101	99	99
Flash Point (COC), °C	ASTM D-92	240	244	246
Pour Point, °C	ASTM D-97	-18	-12	-6
Total Base Number, mg KOH/g	ASTM D-2896	9.4	9.5	9.4

*These typical characteristics mentioned are based on current mean values.



HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from Oculus Lubricant representative.



ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



ADVICE

Advice on application not covered in this leaflet, may be obtained from Oculus Lubricant representative.