

PRODUCT DESCRIPTION

Oculus Lubricant MGX 8000 is an advance heavy duty diesel engine oil formulated with a hydro-treated base oil and a super high performance diesel additive package to provide excellent deposit control to maintain engine power over a longer drain interval.

APPLICATIONS

- Oculus Lubricant MGX 8000 is recommended for 4-stroke heavy duty diesel engines meeting the 2004 exhaust standard.
- Recommended for vehicles which have Exhaust Gas Recirculation (EGR) fitted to give improved engine durability.
- Commercial transport.
- Equally suitable for off-highway vehicles such as vehicles used in construction, quarry and agriculture to carry heavy load and harsh conditions.
- Stationary engines.

PERFORMANCE STANDARD

Superior additive technology used in formulation of Oculus Lubricant MGX 8000 endorses the following performance standards:

| | | | |
|-------------|----------|-------|-------|
| API | CI-4/SL, | ACEA | E7-16 |
| MB-Approval | 228.3 | VOLVO | VDS-3 |

BENEFITS

- Maintains engine power & performance
- Outstanding wear protection
- Longer oil drains in harsh conditions
- Very effective detergent keeps insoluble contaminants suspended in the oil and enhances engine life.

PRODUCT CHARACTERISTICS*

| PROPERTIES | METHOD | TYPICAL RESULTS | |
|-----------------------------------|-------------|-----------------|--------|
| | | 15W-40 | 20W-50 |
| Density @ 15 °C, Kg/liter | ASTM D-4052 | 0.8708 | 0.8799 |
| Kinematic Viscosity @ 100 °C, cSt | ASTM D-445 | 15.52 | 19.7 |
| Kinematic Viscosity @ 40 °C, cSt | ASTM D-445 | 115.9 | 173.8 |
| Viscosity Index | ASTM D-2270 | 141 | 129 |
| Flash Point (COC), °C | ASTM D-92 | 210 | 229 |
| Pour Point, °C | ASTM D-97 | -27 | -21 |
| Total Base Number, mg KOH/g | ASTM D-2896 | 10.3 | 10.3 |

* These typical characteristics mentioned are based on current mean values.



HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from Oculus Lubricant representative.



ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



ADVICE

Advice on application not covered in this leaflet, may be obtained from Oculus Lubricant representative.