

## PRODUCT DESCRIPTION

Oculus Lubricant MX-5 is formulated with an appropriate viscosity grade to meet API SG/CD specifications. The oil is blended with high-quality refined base oils and an advanced additive package to provide improved high-temperature deposits control and lower oil consumption over the life of the oil for passenger cars and light commercial vehicles.

## APPLICATIONS

MX-5 20W-50 motorcycle engine oil is a type of motor oil that is formulated for use in motorcycles with four-stroke engines. is designed to provide protection against engine wear, reduce friction, and prevent the buildup of harmful deposits and contaminants.

**Lubrication:** The primary function of motorcycle engine oil is to lubricate the moving parts of the engine. MX-5 20W-50 oil is designed to provide optimal lubrication and ensure smooth engine operation.

**Protection:** The oil also provides protection against wear and tear, corrosion, and rust. It helps to extend the life of engine components and reduce the risk of engine damage.

**Heat dissipation:** Motorcycle engines can generate a lot of heat during operation. MX-5 20W-50 oil helps to dissipate this heat and maintain optimal engine temperature.

**Performance:** The oil also plays a crucial role in maintaining engine performance. It helps to reduce friction and improve fuel efficiency, which can lead to better acceleration and overall performance.

Overall, MX-5 20W-50 motorcycle engine oil is a versatile and high-quality lubricant that can help to protect and enhance the performance of your motorcycle's engine. However, it's important to always refer to your motorcycle's owner manual for the manufacturer's recommended oil specification and change intervals.

## PRODUCT CHARACTERISTICS\*

PROPERTIES	METHOD	TYPICAL RESULTS-20w50
Density @ 15 °C, Kg/liter	ASTM D-4052	0.9252
Kinematic Viscosity @100 °C, cSt	ASTM D-445	19.87
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	250.5
Viscosity Index	ASTM D-2270	91
Flash Point (COC), °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-6
Total Base Number, mg KOH/g	ASTM D-2896	9.1

\* These typical characteristics mentioned are based on current mean values.



### HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from Oculus Lubricant representative.



### ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



### ADVICE

Advice on application not covered in this leaflet, may be obtained from Oculus Lubricant representative.